

Perfect Cover

Breathable

Perfect Cover Breathable has a impermeable top layer and a self-adhesive underside, which has been specially developed for all hard and smooth floors such as: laminate, PVC, tiles, plastic floors and stairs. Ideally suited for painting, plastering, moving and (re) building. The breathable fleece lets through 1.2 litres per m² per 24 hours.



Technical data



Liquid proof



Shock-resistant



Self-adhesive



Non-slip



Tear resistant



Vapor-permeable

Composition

Top side
Medium
Glue

Multi-layer membrane
Polyester
Dispersion acrylates

Dimensions

Rolls

1m x 25m

1m x 50m

Technical data

| | |
|--------------------------|--------------------------------|
| Color | Blue |
| Weight | 180 g/m ² |
| Fleece thickness | 1.5 mm |
| Tensile strength (CD) | N/5cm 100 |
| Tensile elongation (CD) | % 100 |
| Tensile strength (MD) | N/5cm 100 |
| Tensile elongation (MD) | % 80 |
| Water vapor permeability | 1.2 liter/m ² /24 h |
| Tearing strength (CD) | 1 kg |
| Tearing strength (MD) | 1 kg |

Application

Specially developed for, among others, natural stone and cast floors
Suitable for floors and stairs
Lay down with an overlap of approximately 10 cm, press down securely
NOT suitable for recently poured concrete

Application temperature

Between 5 degrees Celcius and 40 degrees Celcius

Durability

Maximum of 3 months

Remarks

Test the suitability of the product before use
Turn off floor heating before use