

### **Stucvilt Manual & Safety Warning**

### **Product Description**

• Product Name: Stucvilt

• Article number: 23150

• Weight: +/- 120 g/m2

• Type: Floor protector and cover fleece

 Suitable for: Hard and smooth floors such as laminate, PVC, tiles, and plastic floors

• Properties: Absorbent, liquid-tight, reusable, versatile

### **Key Features**

- 1. **Absorbent**: The top layer is a premium polyester non-woven fleece that provides excellent shock, moisture, and paint absorption
- 2. **Versatile**: Suitable for various applications during construction, renovation and painting work.
- 3. **Liquid-tight**: Protects floors from moisture, dirt and paint.
- 4. Reusable: Clean, roll up and reuse the Stucvilt for your next project

### Manual

### **Preparation**

- 1. **Clean the surface**: Make sure the floor is dry, dust-free and clean to ensure optimal adhesion of the cover cardboard.
- 2. **Switching off underfloor heating**: Make sure that the underfloor heating is completely switched off before applying the cover cardboard.



#### Installation

- 1. Roll out: Start on one side of the room and roll out the Stucvilt.
- 2. **Overlap**: Allow the strips to overlap by at least 5 cm for full coverage.
- 3. Mapping: Tape the fleece well with tape where necessary.
- 4. Check: Check that the fleece is securely attached and does not move during use.

#### Removal

- 1. After use: Gently lift the cover fleece, starting at an edge, and fold it carefully.
- 2. **Residue-free removal**: Check the floor for any remaining residue and remove it with a soft cloth if necessary.
- 3. **Store for reuse**: Clean the fleece if necessary, fold it up, and store it in a dry place for future use.
- 4. Waste: After last use, the fleece must be disposed of with the residual waste.

## **Safety Warnings**

- Not suitable for all surfaces: Do not use the cover fleece on freshly laid floors, porous stones, natural stone floors, clay tiles or recently poured concrete.
  Always test on a small, inconspicuous area of the floor first.
- 2. **Limit the duration of use**: Use the cover fleece for a maximum of 3 months to prevent damage to the floor.
- 3. **Do not use with underfloor heating**: Make sure the underfloor heating is turned off to avoid the risk of damage to the fleece.
- 4. **Caution with sharp objects**: Avoid using sharp tools or heavy equipment on the fleece to avoid tearing or damage.
- 5. **Children and pets**: Keep the roll and packaging out of reach of children and pets to avoid the risk of choking.



### **Maintenance and Storage**

- Cleaning: Remove dust, dirt, or spills from the fleece after use with a soft cloth.
- **Storage**: Store unused rolls in a cool, dry place away from direct sunlight and extreme temperatures.
- Reuse: Check the fleece for tears or wear before using it again.

# **Important Notes**

- Always test the cover fleece on a small surface before applying it completely.
- Replace damaged fleece immediately to ensure floor protection.

**Stucvilt** offers a high-quality solution for floor protection during construction and renovation work. Follow this guide for safe and effective use. Contact the supplier for questions or support