

# Perfect Cover

## Vapor-permeable

Perfect Cover Vapor-open has a impermeable top layer and a self-adhesive underside, which has been specially developed for all hard and smooth floors such as: laminate, PVC, tiles, plastic floors and stairs. Ideally suited for painting, plastering, moving and renovation. The breathable fleece lets through 70 grams per m<sup>2</sup> per 24 hours.



### Technical data



Liquid proof



Shock-resistant



Self-adhesive



Non-slip



Tear resistant



Vapor-permeable

#### Composition

Top side	Foil
Medium	Polyester
Glue	Dispersion acrylates

#### Dimensions

Rolls	1m x 25m	1m x 50m
-------	----------	----------

#### Technical data

Color	Blue
Weight	160 g/m <sup>2</sup>
Fleece thickness	1.5 mm
Tensile strength (CD)	N/5cm 100
Tensile elongation (CD)	100% (+/- 10%)
Tensile strength (MD)	N/5cm 100
Tensile elongation (MD)	80% (+/-20%)
Water vapor permeability	70g/m <sup>2</sup> /24h
Tearing strength (CD)	1 kg
Tearing strength (MD)	2 kg

#### Application

Specially developed for recently laid and treated floors  
 For ceramic tiles and wooden floors  
 Suitable for floors and stairs, as well as countertops  
 Lay down with an overlap of approximately 10 cm, press down securely

#### Application temperature

Between 5 degrees Celcius and 40 degrees Celcius

#### Durability

Maximum of 3 months

#### Remarks

Test the suitability of the product before use  
 Turn off floor heating before use