

# Perfect Cover

## ECO

Perfect Cover ECO has a liquid-tight top layer and a self-adhesive underside, which is suitable for all hard and smooth floors such as: laminate, PVC, tiles, plastic floors and stairs. Ideally suited for painting, plastering, moving and building.



### Technical data



Liquid proof



Self-adhesive



Lint-free



Non-slip



Tear resistant

#### Composition

Top side	Foil
Medium	Polyester
Glue	Dispersion acrylates

#### Dimensions

Rolls	1 m x 25 m
-------	------------

#### Technical data

Color	White
Weight	120 g/m <sup>2</sup>
Fleece thickness	1.3 mm
Tensile strength (CD)	N/5cm 80
Tensile elongation (CD)	100% (+/- 10%)
Tensile strength (MD)	N/5cm 80
Tensile elongation (MD)	80% (+/-20%)
Water vapor permeability	N/A
Tearing strength (CD)	1 kg
Tearing strength (MD)	1 kg

#### Application

For all dried-through surfaces  
 Suitable for floors and stairs  
 Lay down with an overlap of approximately 10 cm, press down securely

#### Application temperature

Between 5 degrees Celcius and 40 degrees Celcius

#### Durability

Maximum of 3 months

#### Remarks

Only apply on dried surfaces  
 Test the suitability of the product before use  
 Turn off floor heating before use