

# Perfect Cover

## Fire-retardant

Perfect Cover Fire-retardant has a fire-retardant top layer and a self-adhesive underside, which is suitable for all hard and smooth floors such as: laminate, PVC, tiles, plastic floors and stairs. Ideal for painting, plastering, moving and building.



### Technical data



Liquid proof



Fire-retardant



Self-adhesive



Non-slip



Tear resistant



Shock-resistant

#### Composition

Top side	Fire-retardant PE-foil, B1 class
Medium	Polyester
Glue	Dispersion acrylates

#### Dimensions

Rolls	0.65m x 25m	1m x 25m	1m x 50m
-------	-------------	----------	----------

#### Technical data

Color	White
Weight	180 g/m <sup>2</sup>
Fleece thickness	1.5 mm
Tensile strength (CD)	N/5cm 100
Tensile elongation (CD)	100% (+/- 10%)
Tensile strength (MD)	N/5cm 100
Tensile elongation (MD)	80% (+/-20%)
Fire-retardant (DIN 4102)	B1
Tearing strength (CD)	1 kg
Tearing strength (MD)	2 kg

#### Application

For all dried-through surfaces  
 Suitable for floors and stairs  
 Lay down with an overlap of approximately 10 cm, press down securely

#### Application temperature

Between 5 degrees Celcius and 40 degrees Celcius

#### Durability

Maximum of 3 months

#### Remarks

Only apply on dried surfaces  
 Test the suitability of the product before use  
 Turn off floor heating before use